

## Lithofin TC Classic Primer

### Description

A special product from the LITHOFIN-Range for terracotta (TC). The ready-to-use primer contains silico- and acrylate resins carried in organic solvents.

### Properties

Penetrates into porous surfaces and reduces their absorbency. This treatment renders the surface water repellent and is the precondition for treatment with Lithofin TC Classic Wax.

#### Technical Data:

Density: approx. 0.8 g/cm<sup>3</sup>

pH-Value: n.a.

Flash Point: > 23°C (c.C.)

Appearance: liquid, clear

Odour: aromatic

Solubility in Water: not soluble

### Field of Use

For priming absorbent terracotta and cotto surfaces, especially Italian cotto. This treatment is the first step of the so called "classic" method for treating terracotta. This treatment is not suitable for non-absorbent surfaces and for outdoor use.

### Directions for Use

The surface to be treated must be completely dry and clean. Shake well before use. Try the product in an inconspicuous area in order to evaluate the effect. Evenly apply the undiluted product with a brush or an applicator, avoid streaks and puddles. Even out the coat with a cloth or nylon pad before drying. Start treatment with Lithofin TC Classic Wax immediately after drying (20 to 60 minutes).

Please Note: apply the product only after the silicone joints have been fixed.

Application Temperature: between 10°C and 25°C, turn of underfloor heating.

Drying Time: approx. 60 minutes.

Coverage: approx. 5 to 10m<sup>2</sup> depending on the porosity of the surface.

### Further Treatment

Lithofin TC Classic Wax. Both products belong together in a system known as the "classic" method.

### Storage

Closed, cool and dry. Shelf life of up to 2 years. Open containers should be used quickly.

### Environmental Protection

Contains solvents, free of chlorinated hydrocarbons.

Disposal: liquid product is classified as special waste. Containers are made of environmentally friendly tin plate. Clean containers can be recycled through collection systems.

### Safety

Contents: acrylates; silicones; aliphatic polymers; auxiliary agents.

Risk and Safety Phrases: labelling: Xn, harmful.

May cause cancer. Irritating to eyes and skin.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

Keep out of the reach of children. Do not breathe vapour. Avoid contact with skin. If swallowed, seek medical advice immediately and show this container or label.

First Aid Procedures: remove contaminated soaked clothing immediately. In case of inhalation, move victim to open area. In the event of symptoms refer for medical treatment. In case of contact with skin wash off immediately with soap and water. In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice. In case of ingestion, do not induce vomiting. If swallowed by mistake drink plenty of water and seek medical treatment.

Emergency Procedures: in case of spill or other release, take up with absorbent material (e.g. sand, sawdust, general-purpose binder). In case of fire formation of dangerous gases possible. Suitable extinguishing material: foam, dry powder, carbon dioxide, sand.

Additional Information is listed on the Material Safety Data Sheet.

ADR2003:

labelling: UN1993. Additional comments on freight papers: non, limited quantity.

### Packaging

1 litre bottle with child-proof cap (10 per box)

5 litre canister (2 per box)

This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Where no previous experience is available, or in cases of doubt, test the product in an inconspicuous area. (GB1.06gps/8.03)